



		3H	5H	7PH	5PH	A6500	1PH
Cold Water	Performance (ℓ/h)	2.7	2.7	5	3.2	3.2	2.3
	Tank Volume (ℓ)	3.6	3.3	9.4	3.3	3.3	3.3
	Temp. Range (°C)	1-7	1-7	1.5-7.5	1-7	1-7	1-7
	Compressor Type	Single Phase reciprocating	Single Phase reciprocating	Single Phase reciprocating	Single Phase reciprocating	Single Phase reciprocating	Single Phase reciprocating
	Refrigerant Charge(g)	32	34	46	34	34	30
Hot Water	Performance (ℓ/h)	7	7	7	7	7	7
	Tank Volume (ℓ)	1.6	1.6	1.8	1.6	1.6	1.6
	Temp. Range (°C)	75-93	75-93	77-93	75-93	75-93	75-93
	Heater Type	Sheathed heater	Sheathed heater	Sheathed heater	Sheathed heater	Sheathed heater	Sheathed heater
Dimensions WxDxH	Net (mm)	313x323x972	272x314x970	290x365x1140	272x314x970	272x314x970	272x420x438
	Shipping (mm)	325x325x1020	285x325x1030	305x380x1315	285x325x1120	285x325x1120	285x502x516
Weight	Net (kg)	15	17	23	17	17	12
	Shipping (kg)	17	19	25	19	19	15
Loading Quantity	(EA)	504	560	456	560	544	920
Certificates		NSF, UL, ENERGY STAR	NSF, UL, ENERGY STAR	UL	UL, ENERGY STAR	UL, ENERGY STAR	UL, ENERGY STAR